


| | | |
|---|---|-----------------------------|
|  ISO 9001:2000 CERTIFIED | RISLONE TECHNICAL BULLETIN | |
| | Tech Bulletin #: TB-1201-1 | Page 1 of 1 |
| | Date 1 st Issued: June 6, 2006 | Date Revised: 25 March 2011 |
| | Rislone Super Radiator Flush | Part #: 41201 |

SUPER RADIATOR FLUSH

Rislone Radiator Flush will help your cooling system by removing deposits that build up over time causing overheating. Cleans dirty systems factory clean. Fast, easy and safe to use. Non-acid formula is safe to use on all cooling system materials. Harmless to all parts of the cooling system, including copper and aluminium. Use every time changing antifreeze

| MOST COMMON DIRTY COOLING SYSTEM PROBLEMS | THE SOLUTION, RISLONE SUPER FLUSH |
|---|---|
| <ul style="list-style-type: none"> • Overheating • Deposits & Build Ups | <ul style="list-style-type: none"> • Cleans System • Removes Build Up |



DIRECTIONS

1. Allow engine to cool. Drain system. Close drain.
2. Add entire contents of bottle and refill system with water. For larger cooling systems, use one bottle of Super Radiator Flush for every 15.1 litres. Reinstall cap.
3. Drive for 3 to 6 hours (normal driving) for best results. NOTE: This may be done over several days. If outside temperature is below freezing, this needs to be done in one day to prevent cooling system damage.
4. Allow engine to cool. Flush cooling system and reservoir until water runs clear.
5. Close drain. Refill cooling system and reservoir with manufacturer's recommended antifreeze/water mixture.

| | |
|--------------------|----------------------|
| Part Number: | 41201 |
| UPC Item: | 0 78615 41201 3 |
| UPC Case: | 1 00 78615 41201 0 |
| Bottle Size: | 651ml |
| Bottle Dimensions: | 11.4 x 5.1 x 18.8cm |
| Bottle Cube: | 1093 |
| Case Pack: | 6 bottles per case |
| Case Size: | 23.9 x 16.3 x 20.1cm |
| Case Cube: | 7830 |
| Case Weight: | 5.2kg |
| Pallet: | TI 30 HI 6 Total 180 |
| Pallet Height: | 1.32m |
| Tariff Code: | 3405.90.0000 |

Dosage

Use one bottle of Super Radiator Flush for every 15 litres.