

# Safety Data Sheet

according to Australia WHS and NZ HSNO Regulations

Revision: 25 November 2019

## 1 Identification of the substance/mixture and of the company/undertaking

- **Product identifier**
- **Trade name:** Rislone® Gasoline Treatment – Right Side
- **Product code:** 44700
- **Recommended use and restriction on use**
- **Recommended use:** Treatment for gasoline.
- **Restrictions on use:** No further relevant information available.

- **Details of the supplier of the Safety Data Sheet**

- **Manufacturer/Supplier:**

Rislone  
P.O. Box 187  
Holly, MI 48442  
USA  
Phone: (810) 603-1321



- **Distributor:**

Smits Group Pty Ltd  
59 Greenmount Dr, East Tamaki, Auckland, New Zealand  
NZ Telephone: +09 274 6871  
AUS Telephone 1800883 888

- **Emergency telephone number:**

ChemTel Inc.  
(800)255-3924 (North America)  
+1 (813)248-0585 (International)  
+1-300-954-583 (Australia)

Emergencies within Australia - 131126 (NSW Poison Control Centre)

Emergencies within New Zealand - 0800 764 766 (National Poison Control Centre)

## 2 Hazards identification

- **Classification (Australia, New Zealand)**

Australia NOHSC – Hazardous Substance (Classified according to Worksafe Australia NOHSC 2018 National Code of Practice)

New Zealand HSNO - Hazardous (Classified according to the Minimum Degrees of Hazard Regulations 2001)

- **Hazard statements (New Zealand HSNO Classification)**

HSNO 3.1C Flam. Liq. 3 H226 Flammable liquid and vapour.

HSNO 6.1E Skin Tox. 5 H313 May be harmful in contact with skin.

HSNO 6.1E Inh. Tox. 5 H333 May be harmful if inhaled.

HSNO 6.3B Skin Irr. 3 H316 Causes mild skin irritation.

HSNO 6.1E Asp. Tox 1 H304 May be fatal if swallowed and enters airways

HSNO 9.1C Aquatic Chronic 3 H412 Harmful to aquatic life with long lasting effects.

- **Label elements**

- **Hazard pictograms**



GHS02 GHS08

(Cont'd. on page 2)

# Safety Data Sheet

according to Australia WHS and NZ HSNO Regulations

Revision: 25 November 2019

**Trade name: Rislone® Gasoline Treatment – Right Side**

(Cont'd. from page 1)

- **Signal word** Danger

- **Hazard statements**

H226 Flammable liquid and vapour.  
 H313 May be harmful in contact with skin.  
 H333 May be harmful if inhaled.  
 H316 Causes mild skin irritation.  
 H304 May be fatal if swallowed and enters airways.  
 H412 Harmful to aquatic life with long lasting effects.

- **Precautionary statements**

P210 Keep away from heat/sparks/open flames/hot surfaces. No smoking.  
 P233 Keep container tightly closed.  
 P240 Ground/bond container and receiving equipment.  
 P241 Use explosion-proof electrical/ventilating/lighting equipment.  
 P242 Use only non-sparking tools.  
 P243 Take precautionary measures against static discharge.  
 P273 Avoid release to the environment.  
 P280 Wear protective gloves/protective clothing/eye protection/face protection.  
 P301+P310 IF SWALLOWED: Immediately call a POISON CENTER/ doctor.  
 P331 Do NOT induce vomiting.  
 P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.  
 P304+P312 IF INHALED: Call a POISON CENTER/doctor if you feel unwell.  
 P332+P313 If skin irritation occurs: Get medical advice/attention.  
 P370+P378 In case of fire: Use to extinguish: CO2, powder or water spray.  
 P403+P235 Store in a well-ventilated place. Keep cool.  
 P405 Store locked up.  
 P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

- **Other hazards** There are no other hazards not otherwise classified that have been identified.







- **Results of PBT and vPvB assessment**

- **PBT:** Not applicable.
- **vPvB:** Not applicable.

### 3 Composition/information on ingredients

- **Chemical characterisation: Mixtures**

- **Components:**

CAS: 64742-47-8 EINECS: 265-149-8	Distillates (petroleum), hydrotreated light  Flam. Liq. 3, H226  Asp. Tox. 1, H304 Acute Tox. 5, H313	40-50%
CAS: 64742-95-6	Solvent naphtha (petroleum), light arom.  Flam. Liq. 3, H226  Asp. Tox. 1, H304  STOT SE 3, H336 Acute Tox. 5, H313	<5%
	Polyolefin alkyl phenol alkyl amine  Skin Irrit. 2, H315	<5%

(Cont'd. on page 3)

# Safety Data Sheet

according to Australia WHS and NZ HSNO Regulations

Revision: 25 November 2019

**Trade name: Rislone® Gasoline Treatment – Right Side**

		(Cont'd. from page 2)
CAS: 95-63-6 EINECS: 202-436-9	1,2,4-trimethylbenzene ⚠ Flam. Liq. 3, H226 ⚠ Asp. Tox. 1, H304 ⚠ Aquatic Chronic 2, H411 ⚠ Acute Tox. 4, H332; Skin Irrit. 2, H315; Eye Irrit. 2, H319; STOT SE 3, H335 Acute Tox. 5, H303; Aquatic Acute 2, H401	<2.5%
CAS: 108-67-8 EINECS: 203-604-4	mesitylene ⚠ Flam. Liq. 3, H226 ⚠ Aquatic Chronic 2, H411 ⚠ STOT SE 3, H335	<1.1%
CAS: 128-39-2 EINECS: 204-884-0	2,6-di-tert-butylphenol ⚠ Aquatic Acute 1, H400; Aquatic Chronic 1, H410 ⚠ Skin Irrit. 2, H315	<1%
CAS: 526-73-8 EINECS: 208-394-8	1,2,3-trimethylbenzene ⚠ Flam. Liq. 3, H226 ⚠ STOT RE 2, H373; Asp. Tox. 1, H304 ⚠ STOT SE 3, H335-H336	<1%
CAS: 98-82-8 EINECS: 202-704-5	Cumene ⚠ Flam. Liq. 3, H226 ⚠ Asp. Tox. 1, H304 ⚠ Aquatic Chronic 2, H411 ⚠ Acute Tox. 4, H302; STOT SE 3, H335 Acute Tox. 5, H333	<1%

· **Additional information:** For the wording of the listed Hazard Statements refer to section 16.

## 4 First aid measures

### · Description of first aid measures

#### · After inhalation:

Supply fresh air; consult doctor in case of complaints.  
Provide oxygen treatment if affected person has difficulty breathing.

#### · After skin contact:

Immediately wash with water and soap and rinse thoroughly.  
Seek medical treatment in case of complaints.

#### · After eye contact:

Remove contact lenses if worn.  
Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

#### · After swallowing:

Rinse out mouth and then drink plenty of water.  
Do not induce vomiting; call for medical help immediately.  
A person vomiting while lying on their back should be turned onto their side.

#### · Most important symptoms and effects, both acute and delayed

Coughing  
Dizziness  
Breathing difficulty  
Gastric or intestinal disorders.  
May be harmful in contact with skin.  
May be harmful if inhaled.

(Cont'd. on page 4)

# Safety Data Sheet

according to Australia WHS and NZ HSNO Regulations

Revision: 25 November 2019

**Trade name: Rislone® Gasoline Treatment – Right Side**

(Cont'd. from page 3)

Causes mild skin irritation.

- **Hazards:** Danger of impaired breathing.
- **Indication of any immediate medical attention and special treatment needed**  
 If swallowed, gastric irrigation with added, activated carbon.  
 If swallowed or in case of vomiting, danger of entering the lungs.  
 Medical supervision for at least 48 hours.  
 If necessary oxygen respiration treatment.  
 Later observation for pneumonia and pulmonary oedema.

## 5 Firefighting measures

- **Extinguishing media**
- **Suitable extinguishing agents:**  
 Foam  
 Alcohol resistant foam  
 Gaseous extinguishing agents  
 Carbon dioxide  
 Fire-extinguishing powder  
 Water haze or fog
- **For safety reasons unsuitable extinguishing agents:**  
 Water with full jet  
 Water spray
- **Special hazards arising from the substance or mixture**  
 Formation of toxic gases is possible during heating or in case of fire.
- **Advice for firefighters**
- **Protective equipment:**  
 Wear self-contained respiratory protective device.  
 Wear fully protective suit.
- **Additional information:**  
 Cool endangered receptacles with water fog or haze.  
 Use large quantities of foam as it is partially destroyed by the product.

## 6 Accidental release measures

- **Personal precautions, protective equipment and emergency procedures**  
 Use respiratory protective device against the effects of fumes/dust/aerosol.  
 Keep away from ignition sources.  
 Wear protective equipment. Keep unprotected persons away.  
 Ensure adequate ventilation  
 Particular danger of slipping on leaked/spilled product.
- **Environmental precautions**  
 Do not allow to enter sewers/ surface or ground water.  
 Prevent from spreading (e.g. by damming-in or oil barriers).  
 Inform respective authorities in case of seepage into water course or sewage system.
- **Methods and material for containment and cleaning up**  
 Absorb with non-combustible liquid-binding material (sand, diatomite, acid binders, universal binders).  
 Remove from the water surface (e.g. skim or suck off).  
 Send for recovery or disposal in suitable receptacles.

(Cont'd. on page 5)

# Safety Data Sheet

according to Australia WHS and NZ HSNO Regulations

Revision: 25 November 2019

**Trade name: Rislone® Gasoline Treatment – Right Side**

(Cont'd. from page 4)

· **Reference to other sections**

See Section 7 for information on safe handling.  
See Section 8 for information on personal protection equipment.  
See Section 13 for disposal information.

## 7 Handling and storage

· **Handling:**

· **Precautions for safe handling**

Keep out of reach of children.  
Ensure good ventilation/exhaustion at the workplace.  
Open and handle receptacle with care.  
Avoid breathing mist/vapours/spray.  
Avoid contact with the eyes and skin.

· **Information about fire - and explosion protection:**

Keep respiratory protective device available.  
Keep ignition sources away - Do not smoke.

· **Conditions for safe storage, including any incompatibilities**

· **Requirements to be met by storerooms and receptacles:**

Avoid storage near extreme heat, ignition sources or open flame.  
Store in cool, dry conditions in well sealed receptacles.

· **Information about storage in one common storage facility:**

Store away from foodstuffs.  
Store away from oxidising agents.

· **Specific end use(s)** No further relevant information available.

## 8 Exposure controls/personal protection

· **Control parameters**

· **Ingredients with limit values that require monitoring at the workplace:**

**95-63-6 1,2,4-trimethylbenzene**

REL (USA)	Long-term value: 125 mg/m <sup>3</sup> , 25 ppm
TLV (USA)	Long-term value: 123 mg/m <sup>3</sup> , 25 ppm

**108-67-8 mesitylene**

REL (USA)	Long-term value: 125 mg/m <sup>3</sup> , 25 ppm
TLV (USA)	Long-term value: 123 mg/m <sup>3</sup> , 25 ppm

**526-73-8 1,2,3-trimethylbenzene**

REL (USA)	Long-term value: 125 mg/m <sup>3</sup> , 25 ppm
TLV (USA)	Long-term value: 123 mg/m <sup>3</sup> , 25 ppm

**98-82-8 Cumene**

WES (Australia)	Short-term value: 375 mg/m <sup>3</sup> , 75 ppm Long-term value: 125 mg/m <sup>3</sup> , 25 ppm Sk
PEL (USA)	Long-term value: 245 mg/m <sup>3</sup> , 50 ppm Skin

(Cont'd. on page 6)

# Safety Data Sheet

according to Australia WHS and NZ HSNO Regulations

Revision: 25 November 2019

**Trade name: Rislone® Gasoline Treatment – Right Side**

(Cont'd. from page 5)

REL (USA)	Long-term value: 245 mg/m <sup>3</sup> , 50 ppm Skin
TLV (USA)	Long-term value: (246) NIC-5 mg/m <sup>3</sup> , (50) NIC-1 ppm NIC-A3
WES (New Zealand)	Short-term value: 375 mg/m <sup>3</sup> , 75 ppm Long-term value: 125 mg/m <sup>3</sup> , 25 ppm skin

- **Exposure controls**

- **General protective and hygienic measures:**

Keep away from foodstuffs, beverages and feed.  
Immediately remove all soiled and contaminated clothing.  
Wash hands before breaks and at the end of work.  
Do not inhale gases / fumes / aerosols.  
Avoid contact with the eyes and skin.

- **Respiratory protection:**

Use suitable respiratory protective device in case of insufficient ventilation.  
Use suitable respiratory protective device when aerosol or mist is formed.  
For spills, respiratory protection may be advisable.

- **Protection of hands:**



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

- **Eye protection:**



Safety glasses

- **Body protection:** Protective work clothing

- **Limitation and supervision of exposure into the environment:**

No further relevant information available.

- **Risk management measures:** No further relevant information available.

## 9 Physical and chemical properties

- **Information on basic physical and chemical properties**

- **Appearance**

**Form:** Liquid  
**Colour:** Light yellow  
**Odour:** Petroleum-like  
**Odour threshold:** Not determined.

- **pH-value:** Not determined.

- **Melting point/freezing point:** Not determined.

- **Initial boiling point and boiling range:** >35 °C (>95 °F)

- **Flash point:** 40.6 °C (105.1 °F)

(Cont'd. on page 7)

# Safety Data Sheet

according to Australia WHS and NZ HSNO Regulations

Revision: 25 November 2019

Trade name: Rislone® Gasoline Treatment – Right Side

(Cont'd. from page 6)

· <b>Flammability (solid, gas):</b>	Not applicable.
· <b>Auto/Self-ignition temperature:</b>	Not determined.
· <b>Decomposition temperature:</b>	Not determined.
· <b>Explosive properties:</b>	Product is not explosive. However, formation of explosive air/vapour mixtures are possible.
· <b>Explosion limits</b>	
<b>Lower:</b>	Not determined.
<b>Upper:</b>	Not determined.
· <b>Oxidising properties</b>	Non-oxidising.
· <b>Vapour pressure:</b>	Not determined.
· <b>Density:</b>	
<b>Relative density:</b>	0.77
<b>Vapour density:</b>	Not determined.
<b>Evaporation rate:</b>	Not determined.
· <b>Solubility in / Miscibility with water:</b>	Not miscible or difficult to mix.
· <b>Partition coefficient: n-octanol/water:</b>	Not determined.
· <b>Viscosity</b>	
<b>Dynamic:</b>	Not determined.
<b>Kinematic at 40 °C (104 °F):</b>	1.4 mm <sup>2</sup> /s
· <b>Other information</b>	No further relevant information available.

## 10 Stability and reactivity

- **Reactivity** No further relevant information available.
- **Chemical stability**
- **Thermal decomposition / conditions to be avoided:**  
No decomposition if used and stored according to specifications.
- **Possibility of hazardous reactions**  
Flammable liquid and vapour.  
Used empty containers may contain product gases which form explosive mixtures with air.  
Can form explosive mixtures in air if heated above flash point and/or when sprayed or atomised.  
Reacts with oxidising agents.
- **Conditions to avoid** Excessive heat.
- **Incompatible materials** Oxidisers
- **Hazardous decomposition products** Carbon monoxide and carbon dioxide

## 11 Toxicological information

- **Information on toxicological effects**
- **Acute toxicity:** Based on available data, the classification criteria are not met.
- **LD/LC50 values relevant for classification:** None.

(Cont'd. on page 8)

# Safety Data Sheet

according to Australia WHS and NZ HSNO Regulations

Revision: 25 November 2019

**Trade name: Rislone® Gasoline Treatment – Right Side**

(Cont'd. from page 7)

- **Primary irritant effect**
- **Skin corrosion/irritation:** Based on available data, the classification criteria are not met.
- **Serious eye damage/irritation:** Based on available data, the classification criteria are not met.
- **Respiratory or skin sensitisation:** Based on available data, the classification criteria are not met.
- **IARC (International Agency for Research on Cancer):**  
Present in trace quantities: all except 98-82-8.

98-82-8	Cumene	2B
71-43-2	Benzene	1
75-07-0	acetaldehyde	2B
75-56-9	propylene oxide	2B
91-20-3	Naphthalene	2B
100-41-4	Ethylbenzene	2B
100-42-5	styrene	2B

- **Probable routes of exposure:**  
Ingestion.  
Inhalation.  
Eye contact.  
Skin contact.
- **Germ cell mutagenicity:** Based on available data, the classification criteria are not met.
- **Carcinogenicity:** Based on available data, the classification criteria are not met.
- **Reproductive toxicity:** Based on available data, the classification criteria are not met.
- **STOT-single exposure:** Based on available data, the classification criteria are not met.
- **STOT-repeated exposure:** Based on available data, the classification criteria are not met.
- **Aspiration hazard:** May be fatal if swallowed and enters airways.

## 12 Ecological information

### · Toxicity

#### · Aquatic toxicity:

**128-39-2 2,6-di-tert-butylphenol**

LC50 | 0.89 mg/l (Oncorhynchus mykiss)

- **Persistence and degradability** The product is partially biodegradable. Significant residuals remain.
- **Bioaccumulative potential** Does not accumulate in organisms.
- **Mobility in soil** No further relevant information available.
- **Ecotoxicological effects:**
- **Remark:** Due to mechanical actions of the product (e.g. agglutinations), damages may occur.
- **Additional ecological information:**
- **General notes:** Avoid transfer into the environment.
- **Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **Other adverse effects** No further relevant information available.

## 13 Disposal considerations

(Cont'd. on page 9)



# Safety Data Sheet

according to Australia WHS and NZ HSNO Regulations

Revision: 25 November 2019

**Trade name: Rislone® Gasoline Treatment – Right Side**

(Cont'd. from page 8)

- **Waste treatment methods**

- **Recommendation**

Contact waste processors for recycling information.

The user of this material has the responsibility to dispose of unused material, residues and containers in compliance with all relevant local, state and federal laws and regulations regarding treatment, storage and disposal for hazardous and nonhazardous wastes.

- **Uncleaned packaging:**

- **Recommendation:** Disposal must be made according to official regulations.

## 14 Transport information

- **UN-Number**

- **DOT**

NA1993

- **ADR/RID/ADN, IMDG, IATA**

UN1268

- **UN proper shipping name**

- **DOT**

Combustible liquid, n.o.s. (petroleum distillates)

- **ADR/RID/ADN, IMDG**

PETROLEUM PRODUCTS, N.O.S.

- **IATA**

Petroleum products, n.o.s.

- **Transport hazard class(es)**

- **DOT**



- **Class**

3

- **Label**

3

- **ADR/RID/ADN**



- **Class**

3 (F1)

- **Label**

3

- **IMDG, IATA**



- **Class**

3

- **Label**

3

- **Packing group**

- **DOT, ADR/RID/ADN, IMDG, IATA**

III

- **Environmental hazards:**

(Cont'd. on page 10)




# Safety Data Sheet

according to Australia WHS and NZ HSNO Regulations

Revision: 25 November 2019

**Trade name: Rislone® Gasoline Treatment – Right Side**

(Cont'd. from page 9)

· <b>Marine pollutant:</b>	No
· <b>Special precautions for user</b>	Warning: Flammable liquids.
· <b>Danger code (Kemler):</b>	30
· <b>EMS Number:</b>	F-E,S-E
· <b>Transport in bulk according to Annex II of Marpol and the IBC Code</b>	Not applicable.
· <b>Transport/Additional information:</b>	
· <b>DOT</b>	Classified as combustible under US DOT regulations. Labeling is only required for single packages 119 US gal / 450 L.
· <b>ADR/RID/ADN</b>	
	Limited Quantity for packages less than 30 kg gross and inner packagings less than 5 L each.
· <b>IMDG</b>	
	Limited Quantity for packages less than 30 kg gross and inner packagings less than 5 L each.
· <b>IATA</b>	
	Limited Quantity for packages less than 30 kg gross and inner packagings less than 5 L each / 10 L net.

## 15 Regulatory information

· **Safety, health and environmental regulations/legislation specific for the substance or mixture**

· **IARC (International Agency for Research on Cancer)**

Present in trace quantities: all except 98-82-8.

98-82-8	Cumene	2B
71-43-2	Benzene	1
75-07-0	acetaldehyde	2B
75-56-9	propylene oxide	2B
91-20-3	Naphthalene	2B
100-41-4	Ethylbenzene	2B
100-42-5	styrene	2B
110-00-9	furan	2B

· **Australia**

· **Australian Inventory of Chemical Substances**

(Cont'd. on page 11)

# Safety Data Sheet

according to Australia WHS and NZ HSNO Regulations

Revision: 25 November 2019

**Trade name: Rislone® Gasoline Treatment – Right Side**

(Cont'd. from page 10)

All ingredients are listed or exempt.

· **Standard for the Uniform Scheduling of Medicines and Poisons**

Hydrocarbon Liquids

S5

· **New Zealand HSR002584**

· **New Zealand Inventory of Chemicals (NZIOC)**

All ingredients are listed or exempt.

## 16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· **Relevant phrases**

H226 Flammable liquid and vapour.

H302 Harmful if swallowed.

H303 May be harmful if swallowed.

H304 May be fatal if swallowed and enters airways.

H313 May be harmful in contact with skin.

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H332 Harmful if inhaled.

H333 May be harmful if inhaled.

H335 May cause respiratory irritation.

H336 May cause drowsiness or dizziness.

H373 May cause damage to organs through prolonged or repeated exposure.

H400 Very toxic to aquatic life.

H401 Toxic to aquatic life.

H410 Very toxic to aquatic life with long lasting effects.

H411 Toxic to aquatic life with long lasting effects.

· **Abbreviations and acronyms:**

ADR: European Agreement concerning the International Carriage of Dangerous Goods by Road

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bio-accumulable, Toxic

vPvB: very Persistent and very Bioaccumulative

Flam. Liq. 3: Flammable liquids – Category 3

Acute Tox. 5: Acute toxicity – Category 5

Acute Tox. 4: Acute toxicity – Category 4

Skin Irrit. 2: Skin corrosion/irritation – Category 2

Skin Corr. 3: Skin corrosion/irritation – Category 3

Eye Irrit. 2: Serious eye damage/eye irritation – Category 2

STOT SE 3: Specific target organ toxicity (single exposure) – Category 3

STOT RE 2: Specific target organ toxicity (repeated exposure) – Category 2

Asp. Tox. 1: Aspiration hazard – Category 1

Aquatic Acute 1: Hazardous to the aquatic environment - acute aquatic hazard – Category 1

Aquatic Acute 2: Hazardous to the aquatic environment - acute aquatic hazard – Category 2

Aquatic Acute 3: Hazardous to the aquatic environment - acute aquatic hazard – Category 3

Aquatic Chronic 1: Hazardous to the aquatic environment - long-term aquatic hazard – Category 1

(Cont'd. on page 12)

# Safety Data Sheet

according to Australia WHS and NZ HSNO Regulations

Revision: 25 November 2019

**Trade name: Rislone® Gasoline Treatment – Right Side**

(Cont'd. from page 11)

Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard – Category 2

Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard – Category 3

**• Sources**

Website, European Chemicals Agency (echa.europa.eu)

Website, US EPA Substance Registry Services (ofmpub.epa.gov/sor internet/registry/substreg/home/overview/home.do)

Website, Chemical Abstracts Registry, American Chemical Society (www.cas.org)

Patty's Industrial Hygiene, 6th ed., Rose, Vernon, ed. ISBN: 978-0-470-07488-6

Casarett and Doull's Toxicology: The Basic Science of Poisons, 8th Ed., Klaasen, Curtis D., ed., ISBN: 978-0-07-176923-5.

Safety Data Sheets, Individual Manufacturers

SDS Prepared by:

ChemTel Inc.

1305 North Florida Avenue

Tampa, Florida USA 33602-2902

Toll Free North America 1-888-255-3924 Intl. +01 813-248-0573

Website: www.chemtelinc.com